


AGRIMAX TURF RT 333

| | |
|---------------------|---|
| TIRE SIZE | 480/70 R 34 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAUBENERNTEMASCHINE / ERNTEMASCHINE FÜR OBST / KLEINTRAKTOR / TRACTOR / ERNTEMASCHINE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 149 A8 ; 149 B |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 490 | RIM REC | W 15 L |
| OD (MM) | 1580 | RIM ALT | W 14 L ; W 16 L |
| SLR (MM) | 723 | ECE | E11-106R-009042 |
| RC (MM) | 4785 | SRI | 750 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 50 | 1530 | 1755 | 2015 | 2275 | 2535 | 2795 | 3055 | 3250 |
| 40 | 1530 | 1755 | 2015 | 2275 | 2535 | 2795 | 3055 | 3250 |
| 30 | 1640 | 1880 | 2160 | 2440 | 2715 | 2995 | 3275 | 3480 |
| 10 LT | 2050 | 2355 | 2705 | 3050 | 3400 | 3750 | 4095 | 4355 |
| 10 HT | 1640 | 1880 | 2160 | 2440 | 2715 | 2995 | 3275 | 3480 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.