

# AS 504

<b>TIRE SIZE</b>	<b>4.00 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	66 A8
<b>LI/SS FREE ROLLING</b>	78 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94056576	<b>RC (IN)</b>	76.2
<b>SW (IN)</b>	4.3	<b>RIM REC</b>	3.00 D
<b>OD (IN)</b>	24.7	<b>RIM ALT</b>	2.50 C
<b>SLR (IN)</b>	11.7	<b>ECE</b>	E11-106R-005193

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	1310
15 FR	1110
20 FR	1050
25 FR	940
5 DW	930
15 DW	780
20 DW	740
25 DW	660

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.