


# AGRIMAX RT 945

<b>TIRE SIZE</b>	<b>380/90 R 50</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / TRATOR / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	160 A8/B



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	390	<b>RIM REC</b>	W 12
<b>OD (MM)</b>	1954	<b>RIM ALT</b>	W 11; W 13
<b>SLR (MM)</b>	921	<b>ECE</b>	E11-106R-006446
<b>RC (MM)</b>	5958	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	1845	2385	2880	3195	3375	3690	4005	4275	4500	---
40	1845	2385	2880	3195	3375	3690	4005	4275	4500	---
30	1975	2555	3085	3420	3615	3950	4290	4575	4815	---
10	2670	3450	4165	4620	4880	5335	5790	6180	6505	6750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.