

EARTHMAX SR 34



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 34



EARTHMAX SR 34 is an All Steel radial tire specially engineered and designed for rigid dump trucks working in several operations like mining, quarry, logging and haulage. The non-directional block tread pattern provides excellent traction and stability on any type of terrain. The strong All Steel casing features excellent wear and resistance to any snag and punctures. Its also contributes to an extended tire life-cycle even under the most heavy-duty service condition



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TMPH	O.W. (in)	OD (in)	SLR (in)	RC (in)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø25"	16.00 R 25	TL	E3+	***	183 B	11.25/2.0	-	130	17.3	59.4	27.3	180.1	45.36	CR
	16.00 R 25	TL	E3+	**	177 B	11.25/2.0	-	130	17.3	59.4	27.3	180.1	45.36	CR
	16.00 R 25	TL	E3+	***	183 B	11.25/2.0	-	0	17.3	59.4	27.3	180.1	45.36	UCRC

CR: CUT RESISTANT COMPOUND, UCRC: ULTRA CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index