


AGRIMAX RT 955

| | |
|---------------------|--|
| TYRE SIZE | 300/85 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SPRAYER / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 144 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 295 | RIM REC | W 9 |
| OD (MM) | 1577 | RIM ALT | W 10 ; W 11 |
| SLR (MM) | 745 | ECE | E4-106R-001396 |
| RC (MM) | 4850 | SRI | 750 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1150 | 1485 | 1795 | 1960 | 2100 | 2300 | 2495 | 2660 | 2800 | - |
| 40 | 1150 | 1485 | 1795 | 1960 | 2100 | 2300 | 2495 | 2660 | 2800 | - |
| 30 | 1230 | 1590 | 1920 | 2100 | 2250 | 2460 | 2670 | 2850 | 3000 | - |
| 10 | 1305 | 1640 | 2020 | 2395 | 2775 | 2860 | 3195 | 3530 | 3865 | 4200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.