

AIROMAX AM 27



AIROMAX
RADIAL CRANE TIRES

AIROMAX AM 27



AIROMAX AM 27 is the ideal road-oriented tire for construction applications with cranes. It features extraordinary heat resistance and outstanding riding comfort. AIROMAX AM 27 is a high-speed tire particularly suitable for all operations requiring a high level of handling.



	SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
					REC RIM	ALT RIM					
											
Ø24"	385/95 R 24 (14.00 R 24)	TT	-	170 F	10.00W	-	14.6	53.7	24.6	164.4	STD
Ø25"	445/80 R 25 (17.5R25)	TL	-	170 F	14.00/1.5	14.00/1.3	17.3	53.1	24.8	162.0	STD
	505/95 R 25 (18.00 R 25)	TL	-	186 E	13.00/2.5	-	19.4	63.0	28.7	192.9	STD
	525/80 R 25 (20.5 R 25)	TL	-	176 F	17.00/2.0	17.00/1.7 CR	20.9	58.3	26.8	178.5	STD
	445/95 R 25 (16.00 R 25)	TL	-	174 F	11.25/2.0	11.00/1.7 CR 11.00/1.7 CRL	17.3	58.7	27.4	180.6	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES		
				
				
F	186 lbs			

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026

SIZE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
				REC RIM	ALT RIM					
										
385/95 R 25 (14.00 R 25)	TL	-	170 F	10.00/1.5	-	14.6	53.7	24.6	164.4	STD

STD: STANDARD

TECHNOLOGIES		PERFORMANCES		
   F	  	        	        	Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026