

# AW 702

<b>TIRE SIZE</b>	<b>10.5/80 - 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / REMORCĂ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	138 A8



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	275	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	885	<b>RIM ALT</b>	W 8; 9
<b>SLR (MM)</b>	395	<b>ECE</b>	E11-106R-003577
<b>RC (MM)</b>	2593	<b>PR</b>	14

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>5.10</b>
10 FR	3305
25 FR	2810
30 FR	2645
40 FR	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.