


AGRIMAX RT 855

| | |
|---------------------|--------------------------------------------------------------------------------------------------------------|
| TIRE SIZE | 280/85 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 118 A8/B |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 292 | RIM REC | W 10 |
| OD (MM) | 1187 | RIM ALT | W 9 |
| SLR (MM) | 545 | ECE | E4-106R-000614 |
| RC (MM) | 3558 | SRI | 575 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|-----|------|------|------|------|------|
| 50 | 730 | 845 | 965 | 1085 | 1205 | 1320 |
| 40 | 730 | 845 | 965 | 1085 | 1205 | 1320 |
| 30 | 780 | 910 | 1035 | 1165 | 1290 | 1415 |
| 10 LT | 975 | 1135 | 1295 | 1455 | 1615 | 1770 |
| 10 HT | 780 | 910 | 1035 | 1165 | 1290 | 1415 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.