

AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 340/85 R 46 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 150 A8/B |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 353 | RIM REC | W 12 |
| OD (MM) | 1746 | RIM ALT | W 11 |
| SLR (MM) | 826 | ECE | E4-106R-001828 |
| RC (MM) | 5346 | SRI | 850 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|------|
| 50 | 1445 | 1880 | 2280 | 2480 | 2650 | 2915 | 3150 | 3350 | - |
| 40 | 1445 | 1880 | 2280 | 2480 | 2650 | 2915 | 3150 | 3350 | - |
| 30 | 1545 | 2010 | 2440 | 2655 | 2835 | 3120 | 3370 | 3585 | - |
| 10 | 2065 | 2665 | 3220 | 3520 | 3770 | 4125 | 4475 | 4775 | 5025 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.