


AGRIMAX TERIS

| | |
|---------------------|--|
| TYRE SIZE | IF 710/75 R 34 CFO |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HARVESTER / COTTON PICKER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 184 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 716 | RIM REC | DW 25 B |
| OD (MM) | 1930 | ECE | E11-106R-004899 |
| SLR (MM) | 870 | SRI | 900 |
| RC (MM) | 5852 | | |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 50 | 3510 | 4050 | 4590 | 5220 | 5760 | 6390 | 7110 | 7650 | 8370 | 9000 |
| 40 | 3510 | 4050 | 4590 | 5220 | 5760 | 6390 | 7110 | 7650 | 8370 | 9000 |
| 30 | 3760 | 4335 | 4915 | 5590 | 6165 | 6840 | 7610 | 8190 | 8960 | 9630 |
| 15 CYC* | 5795 | 6685 | 7575 | 8615 | 9505 | 10545 | 11735 | 12625 | 13815 | 14850 |
| 10 CYC* | 6320 | 7290 | 8265 | 9400 | 10370 | 11505 | 12800 | 13770 | 15070 | 16200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.