


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>620/70 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	625	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1833	<b>RIM ALT</b>	DW 18 L; W 18 L
<b>SLR (MM)</b>	828	<b>ECE</b>	E11-106R-005997
<b>RC (MM)</b>	5591	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
<b>65</b>	2340	2760	3180	3540	3960	4320	4740	5100	5580	6000
<b>50</b>	2460	2900	3340	3720	4160	4540	4980	5355	5860	6300
<b>40</b>	2565	3025	3485	3880	4340	4735	5195	5585	6115	6570
<b>30</b>	2695	3175	3660	4075	4555	4970	5455	5865	6420	6900
<b>10 LT</b>	3140	3700	4265	4745	5310	5790	6355	6835	7480	8040
<b>10 HT</b>	2695	3175	3660	4075	4555	4970	5455	5865	6420	6900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.