

# AS 504

<b>TIRE SIZE</b>	<b>7.00 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	ARAMID BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	88 A8
<b>LI/SS FREE ROLLING</b>	100 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94044139	<b>RC (IN)</b>	80.7
<b>SW (IN)</b>	7.4	<b>RIM REC</b>	4.5
<b>OD (IN)</b>	26.9	<b>ECE</b>	E11-106R-003382
<b>SLR (IN)</b>	12.2	<b>PR</b>	8

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>48</b>
<b>5 FR</b>	2470
<b>15 FR</b>	2090
<b>20 FR</b>	1970
<b>25 FR</b>	1760
<b>5 DW</b>	1730
<b>15 DW</b>	1470
<b>20 DW</b>	1380
<b>25 DW</b>	1230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.