


# AGRIMAX V- FLECTO

<b>TIRE SIZE</b>	<b>VF 710/60 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	174 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94514182	<b>RC (IN)</b>	239.8
<b>SW (IN)</b>	28.1	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	80.4	<b>RIM ALT</b>	DW 27 B
<b>SLR (IN)</b>	35.3	<b>ECE</b>	E11-106R-0011234

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	14	17	20	23
45	7400	8610	9820	11030	12250	13450
<b>FROM 40 TO 25</b>	8120	9460	10790	12110	13450	14770
20	8290	9640	11000	12360	13710	15070
12	8450	9840	11220	12610	13990	15370
5	8940	10410	11870	13330	14790	16250
<b>UPTO 20 CYC</b>	9230	10740	12250	13760	15270	16770
<b>UPTO 10 CYC</b>	11010	12820	14620	16420	18220	20020
<b>UPTO 5CYC</b>	12070	14040	16020	17990	19960	21930
5 HT	8290	9640	11000	12360	13710	15070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.