


# TR 463

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>18.4 - 26</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TERNA / TRATTORE INDUSTRIALE   |
| <b>VERSIONE</b>     | INDUSTRIAL   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 158 A8   |



## DIMENSIONI US STANDARD

|                   |          |                |                  |
|-------------------|----------|----------------|------------------|
| <b>CODICE USA</b> | 94515073 | <b>RC (IN)</b> | 165.9            |
| <b>SW (IN)</b>    | 18.9     | <b>RIM REC</b> | DW 16 L          |
| <b>OD (IN)</b>    | 56.1     | <b>RIM ALT</b> | DW 15 L          |
| <b>SLR (IN)</b>   | 25.1     | <b>ECE</b>     | E11-106R-0011590 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>42</b> |
| 25               | 9350      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.