

RIB 774 (A)

| | |
|---------------------------|---|
| TIRE SIZE | 250/65 - 14.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ПРЕСС-ПОДБОРЩИК / КОМБАЙН / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 124 A8 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94027255 | RC (IN) | 77.9 |
| SW (IN) | 10.0 | RIM REC | AG 8.00 |
| OD (IN) | 27.2 | RIM ALT | 6.75 |
| SLR (IN) | 11.9 | ECE | E11-106R-003374 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 80 |
|-----------|------|
| 5 FR | 4940 |
| 15 FR | 4200 |
| 20 FR | 3950 |
| 25 FR | 3530 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.