


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>580/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	180 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94038510	<b>RC (IN)</b>	216.7
<b>SW (IN)</b>	22.7	<b>RIM REC</b>	W 18 L
<b>OD (IN)</b>	71.9	<b>ECE</b>	E4-106R-000809
<b>SLR (IN)</b>	32.3	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58	64	67
30	7010	8540	9900	11000	12040	12980	13910	14790	15630	16050
25	7010	8540	10870	12080	13230	14260	15280	16250	17170	17640
20	7510	9150	11640	12920	14150	15260	16360	17390	18390	18870
15	7790	9490	12060	13400	14680	15830	16950	18030	19070	19580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.