


AGRIMAX RT 765M

TIRE SIZE	710/70 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	175 D ; 178 A8



DIMENSIONS IS STANDARD

SW (MM)	716	RIM REC	DW 23 B
OD (MM)	1959	ECE	E11-106R-004072
SLR (MM)	859	SRI	925
RC (MM)	5751	TRA CODE	R1W

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2895	3325	3815	4305	4800	5290	5785	6150
50	3040	3490	4010	4525	5040	5560	6075	6460
40	3150	3620	4155	4690	5230	5765	6300	6700
30	3330	3825	4390	4955	5520	6085	6655	7075
10 LT	3880	4455	5115	5775	6435	7095	7755	8245
10 HT	3330	3825	4390	4955	5520	6085	6655	7075

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.