DATA SHEET

PRINTED ON
23-04-2026

AIROMAX AM 27

TIRE SIZE	**445/95 R 25**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	GUINDASTE MÓVEL
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	174 F

DIMENSÕES US STANDARD

CÓDIGO USA	94039043	**RIM REC**	11.25/2.0
OD (IN)	58.7	**RIM ALT**	11.00/1.7 CR; 11.00/1.7CRL
SLR (IN)	27.4	**ECE**	E4-54R-0028867
RC (IN)	180.6		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	130
20	18700
25	17100
30	16500
35	16100
43	15700
50	14800
55	13900
62	12300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..