

# TR 144

|                     |                        |
|---------------------|------------------------|
| <b>TIRE SIZE</b>    | <b>8 - 16</b>          |
| <b>UM</b>           | IS STANDARD            |
| <b>CONSTRUCTION</b> | ❖ BIAS                 |
| <b>MACHINERY</b>    | KLEINTRAKTOR / TRACTOR |
| <b>VERSION</b>      | STANDARD               |
| <b>TIRE TYPE</b>    | TT                     |
| <b>LI/SS</b>        | 98 A6                  |



## ABMESSUNGEN IS STANDARD

|                 |      |                 |                   |
|-----------------|------|-----------------|-------------------|
| <b>SW (MM)</b>  | 200  | <b>RIM REC</b>  | 6 L; 6 LB; 6.00 F |
| <b>OD (MM)</b>  | 785  | <b>ECE</b>      | E11-106R-004325   |
| <b>SLR (MM)</b> | 358  | <b>PR</b>       | 8                 |
| <b>RC (MM)</b>  | 2342 | <b>TRA CODE</b> | R1                |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.60</b> |
| 30                | 750         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.