


MULTIMAX MP 522

TIRE SIZE	480/80 R 26
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ÎNCĂRCĂTOR COMPACT / ÎNCĂRCĂTOR TELESCOPIC / ÎNCĂRCĂTOR COMPACT / ÎNCĂRCĂTOR TELESCOPIC
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	160 A8/B



DIMENSIUNI IS STANDARD

SW (MM)	479	RIM REC	DW 15 L
OD (MM)	1428	RIM ALT	DW 16 L
SLR (MM)	638	ECE	E11-106R-002970
RC (MM)	4287	SRI	675

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
50	2610	3060	3330	3555	3780	4005	4275	4500	-	-
40	2610	3060	3330	3555	3780	4005	4275	4500	-	-
30	2795	3275	3565	3805	4045	4290	4575	4815	-	-
25	2900	3400	3700	3950	4200	4450	4750	4995	-	-
10 CYC.	3175	3915	4255	4590	4995	5335	5670	6075	6415	6750
STATIC	4865	6005	6525	7040	7660	8180	8695	9315	9835	10350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.