

# PRO RIB F2M

|                     |                                       |
|---------------------|---------------------------------------|
| <b>TIRE SIZE</b>    | 14L - 16.1 SL                         |
| <b>UM</b>           | US STANDARD                           |
| <b>CONSTRUCTION</b> | ❖ BIAS                                |
| <b>MACHINERY</b>    | TRACTEUR 2WD / TRACTEUR /<br>REMORQUE |
| <b>VERSION</b>      | STANDARD                              |
| <b>TIRE TYPE</b>    | TL                                    |
| <b>LI/SS</b>        | 127 A8                                |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>CODE USA</b> | 94020485 | <b>RC (IN)</b> | 115.0          |
| <b>SW (IN)</b>  | 14.0     | <b>RIM REC</b> | W 11 C         |
| <b>OD (IN)</b>  | 38.6     | <b>ECE</b>     | E4-106R-002331 |
| <b>SLR (IN)</b> | 17.8     | <b>PR</b>      | 12             |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>52</b> |
| 25               | 3860      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.