

CON STAR



CON STAR



CON STAR is particularly suitable for compact loaders and telehandlers in agroindustrial, lifting and loading applications. It features great traction along with excellent vertical and horizontal stability. CON STAR has been made of a cut-and-chip-resistant compound contributing to an extended tire life-cycle.



	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø18"	340/80 - 18 (12.5/80 - 18)	143 A8	11	12 11 SDC 12 SDC W 10 W 11	13.8	40.0	18.3	119.7	475	IND
Ø20"	400/70 - 20 (16.0/70 - 20)	156 A8	13	12 SDC 13 SDC 14	15.9	42.5	19.7	130.0	525	IND
	400/70 - 20 (16.0/70 - 20)	149 A8	13	12 SDC 13 SDC 14	15.9	42.5	19.7	130.0	525	IND
	340/80 - 20 (12.5/80 - 20)	144 A8	11	12 11 SDC 12 SDC W 10 W 11	13.8	41.9	19.3	128.8	500	IND
	400/70 - 20 (16.0/70 - 20)	161 A8	13	12 SDC 13 SDC 14	15.9	42.5	19.5	122.3	525	IND

IND: INDUSTRIAL

TECHNOLOGIES		PERFORMANCES	
			  
			
A8	168 lbs		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	380/75 - 20 (14.5 - 20)	148 A8	W 12	W 11 12 SDC 12 W 13 13 SDC 13	15.2	42.5	19.7	128.9	-	IND
Ø24"	460/70 - 24 (17.5L - 24)	159 A8	DW 15 L	DW 14 L DW 16 L	18.1	49.2	22.1	149.0	600	IND
	500/70 - 24 (19.5L - 24)	164 A8	DW 16 L	DW 15 L DW 18 L	19.9	51.2	22.8	154.6	625	IND
	440/80 - 24 (17.0/80 - 24)	168 A8	DW 14 L	DW 13 DW 13 L DW 15 L	17.9	51.8	23.78	160.51	625	IND
	400/70 - 24 (16.0/70 - 24)	158 A8	13	DW 12 13 SDC DW 13 DW 13 L DW 14 L	15.6	46.3	21.4	140.0	575	IND
	400/80 - 24 (15.5/80 - 24)	162 A8	DW 13	DW 12 DW 13 L DW 14 L	15.9	49.2	22.4	148.9	600	IND
Ø26"	480/80 - 26 (18.4 - 26)	160 A8	DW 15 L	DW 16 L	19.3	55.5	25.3	168.2	675	IND
Ø28"	440/80 - 28 (16.9 - 28)	156 A8	DW 14 L	DW 13 DW 13 L DW 15 L	17.7	55.9	24.9	169.3	675	IND

IND: INDUSTRIAL

TECHNOLOGIES		PERFORMANCES	
			  
			
A8	168 lbs		Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US - 15/07/2026