


AGRIMAX TERIS

| | |
|---------------------|--|
| TYRE SIZE | 520/85 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 168 D |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|---|
| SW (MM) | 516 | RIM REC | DW 16 L |
| OD (MM) | 1951 | RIM ALT | W15L; DW15L; DD16L; W16L; DD18L; DW18L; W18L |
| SLR (MM) | 890 | ECE | E4-106R-001829 |
| RC (MM) | 5851 | SRI | 925 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.8 |
|------------|------|------|------|------|------|------|------|------|------|------|------|
| 65 | 1850 | 2185 | 2520 | 2800 | 3140 | 3420 | 3980 | 4540 | 5100 | 5600 | - |
| 50 | 1945 | 2295 | 2650 | 2940 | 3295 | 3590 | 4175 | 4765 | 5355 | 5880 | - |
| 40 | 2025 | 2395 | 2765 | 3070 | 3440 | 3745 | 4360 | 4970 | 5585 | 6135 | - |
| 30 | 2130 | 2515 | 2900 | 3220 | 3610 | 3930 | 4575 | 5250 | 5865 | 6440 | - |
| 25 | 2195 | 2590 | 2990 | 3320 | 3720 | 4055 | 4715 | 5380 | 6045 | 6640 | - |
| 10 | 2775 | 3280 | 3780 | 4200 | 4705 | 5125 | 5965 | 6805 | 7645 | 8400 | - |
| 10 CYC* | - | - | - | - | - | - | - | - | - | - | 9520 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.