




PRINTED ON  
21-04-2026

## DATA SHEET

# FL 252

<b>TIRE SIZE</b>	<b>5.00 - 8</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ADAINEUR ROTATIF / OUTILLAGE AGRICOLE / CHARIOT ÉLEVATEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT



### DIMENSIONS US STANDARD

<b>CODE USA</b>	94006816	<b>RIM ALT</b>	3.25 I
<b>SW (IN)</b>	5.4	<b>PR</b>	8
<b>OD (IN)</b>	18.9		
<b>RIM REC</b>	3.00 D		

### LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>120</b>
<b>15 LOAD WHEEL</b>	2725
<b>15 STEER WHEEL</b>	2095
<b>5 OTHER VEHICLES</b>	2725
<b>15 OTHER VEHICLES</b>	2095
<b>STATIC SIDE LOADER</b>	3165

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.