

AS 509

| | |
|---------------------------|--|
| TIRE SIZE | 550/45 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | BALER / IMPLEMENT MACHINERY / TRAILER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 141 A8/137 B |
| LI/SS FREE ROLLING | 153 A8/149 B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 540 | RIM REC | AG 16.00 |
| OD (MM) | 1065 | ECE | E11-106R-006445 |
| SLR (MM) | 479 | PR | 12 |
| RC (MM) | 3250 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.50 | 1.80 | 2.10 |
|------------|------|------|------|
| 10 FR | 4200 | 4670 | 5110 |
| 20 FR | 3780 | 4200 | 4600 |
| 30 FR | 3360 | 3735 | 4090 |
| 40 FR | 3000 | 3335 | 3650 |
| 50 FR | 2700 | 3000 | 3250 |
| 10 DW | 2960 | 3295 | 3605 |
| 20 DW | 2665 | 2965 | 3245 |
| 30 DW | 2370 | 2640 | 2885 |
| 40 DW | 2115 | 2355 | 2575 |
| 50 DW | 1905 | 2120 | 2300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.