


AGRIMAX V- FLECTO

TIRE SIZE	VF 650/75 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	SPECIAL
TIRE TYPE	TL
LI/SS	180 D



DIMENSIONI IS STANDARD

SW (MM)	680	RIM REC	DW 23 B
OD (MM)	2055	RIM ALT	DW 21 B
SLR (MM)	895	ECE	E11-106R-0011304
RC (MM)	6143	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2
70	3640	4220	4800	5460	6040	6620	7280
FROM 65 TO 40	4000	4640	5280	6000	6640	7280	8000
30	4080	4730	5385	6120	6770	7425	8160
20	4160	4825	5490	6240	6905	7570	8320
10	4400	5100	5805	6600	7300	8005	8800
UPTO 30 CYC	4540	5265	5990	6810	7535	8260	9080
UPTO 15 CYC	5420	6285	7150	8130	8995	9860	10840
UPTO 10 CYC	5940	6890	7840	8910	9860	10810	11880
10HT	4080	4730	5385	6120	6770	7425	8160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.