

FL 630 SUPER

| | |
|---------------------|--|
| TIRE SIZE | 600/55 R 26.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | РАЗБРАСЫВАТЕЛЬ / АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 165 D |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94040476 | RC (IN) | 160.6 |
| SW (IN) | 24.1 | RIM REC | AG 20.00 |
| OD (IN) | 52.5 | ECE | E4-106R-001414 |
| SLR (IN) | 23.9 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 3320 | 3840 | 4340 | 5280 | 6110 | 7030 | 7970 | 8590 | 9510 | 10340 |
| 40 | 3640 | 4210 | 4770 | 5800 | 6700 | 7730 | 8750 | 9420 | 10450 | 11350 |
| 30 | 4410 | 5090 | 5780 | 7010 | 8110 | 9350 | 10590 | 11420 | 12650 | 13750 |
| 25 | 4950 | 5720 | 6490 | 7880 | 9120 | 10500 | 11890 | 12820 | 14210 | 15440 |
| 15 | 5740 | 6650 | 7540 | 9160 | 10590 | 12210 | 13820 | 14900 | 16510 | 17940 |
| 5 | 6550 | 7570 | 8590 | 10430 | 12060 | 13900 | 15740 | 16960 | 18800 | 20440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.