


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>440/65 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VENDIMIADORA / TRACTOR / COSECHADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	135 D ; 138 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	441	<b>RIM REC</b>	W 14 L
<b>OD (MM)</b>	1182	<b>RIM ALT</b>	W 13; W 15 L
<b>SLR (MM)</b>	538	<b>ECE</b>	E4-106R-000616
<b>RC (MM)</b>	3546	<b>SRI</b>	575

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1050	1225	1375	1530	1680	1810	2010	2180
<b>50</b>	1100	1285	1445	1605	1765	1905	2110	2290
<b>40</b>	1135	1325	1490	1655	1820	1960	2175	2360
<b>30</b>	1205	1410	1585	1760	1935	2085	2310	2510
<b>10 LT</b>	1405	1640	1845	2050	2255	2430	2695	2925
<b>10 HT</b>	1205	1410	1585	1760	1935	2085	2310	2510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.