

# TR 459

|                     |  |
|---------------------|--|
|                     | <b>19.5L - 24</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRAKTÖR / BEKOLODER / BEKOLODER  |
| <b>VERSION</b>      | INDUSTRIAL SPECIAL   |
| <b>TIRE TYPE</b>    | TL   |
|                     | 151 A8   |



## UNDEFINED US STANDARD

|                 |          |                 |         |
|-----------------|----------|-----------------|---------|
| <b>USA CODE</b> | 94035625 | <b>RC (IN)</b>  | 158.7   |
| <b>SW (IN)</b>  | 19.3     | <b>RIM REC</b>  | DW 16 L |
| <b>OD (IN)</b>  | 52.5     | <b>PR</b>       | 12      |
| <b>SLR (IN)</b> | 23.0     | <b>TRA CODE</b> | R4      |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>34</b> |
| 25               | 7600      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.