


# AS 504

<b>TIRE SIZE</b>	<b>5.00 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	67 A8
<b>LI/SS FREE ROLLING</b>	79 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94019144	<b>RC (IN)</b>	77.0
<b>SW (IN)</b>	5.5	<b>RIM REC</b>	3.50 D
<b>OD (IN)</b>	25.9	<b>RIM ALT</b>	3.00 D; 4.00 E; 4 J
<b>SLR (IN)</b>	12.1	<b>ECE</b>	E11-106R-004237

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33
5 FR	1340
15 FR	1150
20 FR	1070
25 FR	960
5 DW	940
15 DW	800
20 DW	750
25 DW	670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.