


AGRIMAX RT 955

TIRE SIZE	270/80 R 32
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ARBETSFORDON / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	131 A8/B



DIMENSIONER IS STANDARD

SW (MM)	270	RIM REC	W 9
OD (MM)	1225	RIM ALT	W 8 ; W 10
SLR (MM)	569	ECE	E11-106R-0011741
RC (MM)	3711	SRI	600

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2	2.4	2.8	3.2	3.6	4
50	685	800	920	1035	1155	1250	1385	1465	1600	1740	1855	1950
40	685	800	920	1035	1155	1250	1385	1465	1600	1740	1855	1950
30	735	860	985	1110	1235	1340	1485	1570	1715	1865	1990	2090
10	1025	1200	1375	1555	1730	1875	2080	2195	2400	2605	2780	2925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.