


# FL 630 SUPER

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>850/50 R 30.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | STREUMASCHINE / TANKWAGEN / ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE                        |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 182 D  |



## ABMESSUNGEN US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA-CODE</b> | 94073191 | <b>RC (IN)</b> | 192.7           |
| <b>SW (IN)</b>  | 33.9     | <b>RIM REC</b> | AG 28.00        |
| <b>OD (IN)</b>  | 64.0     | <b>ECE</b>     | E11-106R-008232 |
| <b>SLR (IN)</b> | 28.4     |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17    | 23    | 29    | 35    | 41    | 46    | 52    | 58    |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45        | 7000  | 8700  | 9900  | 11430 | 12960 | 14160 | 15520 | 17050 |
| 40        | 7680  | 9560  | 10870 | 12550 | 14240 | 15550 | 17050 | 18740 |
| 30        | 9300  | 11570 | 13160 | 15200 | 17240 | 18830 | 20630 | 22670 |
| 25        | 10450 | 13010 | 14780 | 17080 | 19380 | 21150 | 23190 | 25480 |
| 15        | 12150 | 15100 | 17170 | 19840 | 22510 | 24580 | 26950 | 29610 |
| 5         | 13830 | 17210 | 19560 | 22610 | 25640 | 28000 | 30700 | 33730 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.