


# EARTHMAX SR 49 M

<b>TIRE SIZE</b>	29.5 R 29
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BULDOZER / BASCULARE ÎNCĂRCĂTURI (LHD) / ÎNCĂRCĂTOR / AUTOBASCULANTĂ CU PROFIL REDUS (LPDT)
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	223 A2



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94052400	<b>RIM REC</b>	25.00/3.5
<b>OD (IN)</b>	79.0	<b>RIM ALT</b>	24.00/3.5;26.00/3.5
<b>SLR (IN)</b>	35.7	<b>TRA CODE</b>	L4
<b>RC (IN)</b>	248.8	<b>STAR RATING</b>	★★★

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	98	102	105	109	112	116
5	53600	55100	56800	57800	58900	60000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.