

AW 09

260/70 - 15.3

| | |
|---------------------|---|
| UM | IS STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | BALYA MAKINESİ / UYGULAMALI MAKİNE / RÖMÖRK / BIÇERDÖVER / UYGULAMALI MAKİNE / BIÇERDÖVER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 119 A8 |
| | 131 A8 |



UNDEFINED IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 268 | RIM REC | 9.00 |
| OD (MM) | 753 | ECE | E4-106R-000374 |
| SLR (MM) | 335 | | |
| RC (MM) | 2206 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.00 |
|------------|------|
| 10 FR | 2730 |
| 25 FR | 2320 |
| 30 FR | 2185 |
| 40 FR | 1950 |
| 10 DW | 1905 |
| 25 DW | 1620 |
| 30 DW | 1525 |
| 40 DW | 1360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.