

AGRIMAX SPARGO SB

TIRE SIZE	VF 380/90 R 54
UM	IS STANDARD
CONSTRUCTION	
MACHINERY	TRACTOR / SPRAYER
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	176 D



DIMENSIONS IS STANDARD

SW (MM)	395	RIM REC	W13
OD (MM)	2060	RIM ALT	W12;DW12;W13A; DW13;DW13A
SLR (MM)	957	ECE	E11-106R-0010178
RC (MM)	6310	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4
70	2780	3105	3495	3815	4010	4205	4335	4465	4690	4915	5110	5305	5465	5625	5790	5950	6210	6465
FROM 65 TO 40	3055	3410	3835	4190	4405	4615	4760	4900	5150	5400	5610	5825	6000	6180	6355	6535	6820	7100
30	3120	3480	3915	4275	4495	4710	4855	5000	5255	5510	5725	5945	6125	6305	6485	6670	6960	7245
20	3180	3545	3990	4360	4580	4805	4950	5100	5355	5615	5835	6060	6245	6425	6610	6795	7090	7385
10	3360	3750	4220	4610	4845	5080	5235	5390	5665	5940	6170	6405	6600	6795	6990	7190	7500	7810
UPTO 30 CYC	3470	3870	4355	4760	5000	5240	5405	5565	5845	6130	6370	6610	6815	7015	7215	7420	7740	8060
UPTO 15 CYC	4140	4620	5200	5680	5970	6260	6450	6645	6980	7315	7605	7895	8135	8375	8615	8855	9240	9625
UPTO 10 CYC	4535	5065	5695	6225	6540	6855	7070	7280	7650	8015	8335	8650	8915	9175	9440	9705	10125	10545
10 HT	3120	3480	3915	4275	4495	4710	4855	5000	5255	5510	5725	5945	6125	6305	6485	6670	6960	7245

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.