


FORESTMAX

TIRE SIZE	650/65 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR / AUTOCARREGADORA
VERSÃO	STEEL BELTED
TIRE TYPE	TL
LI/SS	164 A8 ; 160 B



DIMENSÕES IS STANDARD

SW (MM)	645	RIM REC	DW 20 B
OD (MM)	1811	RIM ALT	DW21B; DW23B
SLR (MM)	832	ECE	E11-106R-008829
RC (MM)	5467	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2.0	2.2	2.4
50	3060	3420	3510	3870	4185	4320	4500
40	3400	3800	3900	4300	4650	4800	5000
30	3640	4070	4175	4600	4975	5140	5350
25	3775	4220	4330	4775	5160	5330	5550
20	4185	4675	4795	5290	5715	5905	6150
15	4560	5095	5225	5760	6230	6435	6700
10	5100	5700	5850	6450	6970	7200	7500
10 FORESTRY SERVICE	-	-	-	-	-	-	6150
0 FORESTRY SERVICE	-	-	-	-	-	-	11500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.