


FL 630 SUPER

| | |
|---------------------|--|
| TIRE SIZE | 560/60 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | STREUMASCHINE / TANKWAGEN / ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 161 D |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA-CODE | 94042166 | RC (IN) | 149.0 |
| SW (IN) | 21.4 | RIM REC | AG 16.00 |
| OD (IN) | 49.0 | RIM ALT | 17.00; 20.00 |
| SLR (IN) | 21.6 | ECE | E4-106R-000794 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 45 | 3000 | 3470 | 3940 | 4680 | 5530 | 6330 | 7030 | 7870 | 8620 | 9370 |
| 40 | 3260 | 3780 | 4290 | 5100 | 6020 | 6890 | 7650 | 8560 | 9380 | 10200 |
| 30 | 3960 | 4570 | 5190 | 6170 | 7290 | 8330 | 9260 | 10370 | 11360 | 12350 |
| 25 | 4440 | 5140 | 5830 | 6930 | 8190 | 9370 | 10410 | 11650 | 12760 | 13870 |
| 15 | 5160 | 5970 | 6780 | 8060 | 9510 | 10880 | 12090 | 13550 | 14840 | 16110 |
| 5 | 5870 | 6800 | 7720 | 9180 | 10840 | 12390 | 13770 | 15420 | 16890 | 18350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.