


AGRIMAX V- FLECTO

| | |
|--------------|--|
| TIRE SIZE | VF 900/60 R 42 CFO |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR / TRACTOR DE ALTA POTENCIA |
| VERSIÓN | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 189 D |



DIMENSIONES IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 900 | RIM REC | DW 30B |
| OD (MM) | 2142 | ECE | E11-106R-006165 |
| SLR (MM) | 931 | SRI | 1025 |
| RC (MM) | 6390 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1 | 1.2 | 1.4 | 1.6 | 2 |
|---------------|------|------|-------|-------|-------|-------|-------|
| 70 | 4590 | 5340 | 6180 | 6930 | 7680 | 8435 | 9370 |
| FROM 65 TO 40 | 5045 | 5870 | 6795 | 7620 | 8445 | 9270 | 10300 |
| 30 | 5145 | 5985 | 6930 | 7770 | 8610 | 9455 | 10505 |
| 20 | 5245 | 6100 | 7065 | 7920 | 8780 | 9640 | 10710 |
| 10 | 5545 | 6455 | 7470 | 8380 | 9285 | 10195 | 11330 |
| UPTO 30 CYC | 5730 | 6665 | 7720 | 8655 | 9590 | 10525 | 11690 |
| UPTO 15 CYC | 6840 | 7955 | 9215 | 10330 | 11445 | 12560 | 13955 |
| UPTO 10 CYC | 7495 | 8720 | 10095 | 11320 | 12545 | 13770 | 15295 |
| 10 HT | 5145 | 5985 | 6930 | 7770 | 8610 | 9455 | 10505 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.