


AGRIMAX FORCE

| | |
|--------------|--|
| TIRE SIZE | IF 900/50 R 42 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CEIFEIRA / TRATOR DE ALTA POTENCIA / TRATOR |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 180 D |



DIMENSÕES IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 881 | RIM REC | DW 30 B |
| OD (MM) | 1955 | RIM ALT | TW 30 B |
| SLR (MM) | 872 | ECE | E11-106R-006492 |
| RC (MM) | 5830 | SRI | 950 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|---------------|------|------|------|------|-------|-------|-------|-------|
| 70 | 3345 | 3855 | 4440 | 4950 | 5530 | 6040 | 6770 | 7280 |
| FROM 65 TO 40 | 3680 | 4240 | 4880 | 5440 | 6080 | 6640 | 7440 | 8000 |
| 30 | 3825 | 4405 | 5075 | 5655 | 6320 | 6905 | 7735 | 8320 |
| 20 | 3970 | 4575 | 5270 | 5875 | 6565 | 7170 | 8035 | 8640 |
| 10 | 4670 | 5380 | 6195 | 6905 | 7720 | 8430 | 9445 | 10160 |
| UPTO 30 CYC | 4780 | 5510 | 6340 | 7070 | 7900 | 8630 | 9670 | 10400 |
| UPTO 15 CYC | 5700 | 6570 | 7560 | 8430 | 9420 | 10290 | 11530 | 12400 |
| UPTO 10 CYC | 6255 | 7205 | 8295 | 9245 | 10335 | 11285 | 12645 | 13600 |
| 10HT | 3825 | 4405 | 5075 | 5655 | 6320 | 6905 | 7735 | 8320 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.