

AGRIMAXFACTOR

TIRE SIZE	600/70 R 28
UM	IS STANDARD
MACHINERY	ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	157 D ; 160 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	611	ECE	E11-106R-007655
OD (MM)	1551	SRI	725
SLR (MM)	714	TRA CODE	R1W
RC (MM)	4667	TREAD DEPTH (MM)	57
RIM REC	DW 20 B	TKPH (TK/H)	0
RIM ALT	DW 18 L ; W 18 L		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1940	2230	2560	2890	3220	3550	3880	4125
50	2040	2345	2690	3035	3385	3730	4075	4335
40	2125	2445	2805	3165	3530	3890	4250	4520
30	2235	2565	2945	3325	3705	4085	4465	4745
10 LT	2600	2990	3430	3875	4315	4760	5200	5530
10HT	2235	2565	2945	3325	3705	4085	4465	4745

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.