

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 480/70 R 24 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 138 D |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 479 | RIM REC | W 15 L |
| OD (MM) | 1316 | RIM ALT | W 14 L; W 16 L |
| SLR (MM) | 580 | ECE | E11-106R-005519 |
| RC (MM) | 3894 | SRI | 625 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 1300 | 1515 | 1725 | 1940 | 2150 | 2360 |
| 50 | 1365 | 1590 | 1815 | 2035 | 2260 | 2480 |
| 40 | 1425 | 1655 | 1890 | 2120 | 2355 | 2585 |
| 30 | 1495 | 1740 | 1985 | 2230 | 2475 | 2715 |
| 10 LT | 1745 | 2030 | 2315 | 2600 | 2885 | 3165 |
| 10 HT | 1495 | 1740 | 1985 | 2230 | 2475 | 2715 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.