


# MULTIMAX SR 261

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>215/75 R 17.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | LOW PLATFORM TRAILER / MOBILE CRANE  |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 135/133 J  |



## DIMENSIONS US STANDARD

|                 |          |                |      |
|-----------------|----------|----------------|------|
| <b>USA CODE</b> | 94071067 | <b>RIM REC</b> | 6.00 |
| <b>OD (IN)</b>  | 30.5     | <b>RIM ALT</b> | 6.75 |
| <b>SLR (IN)</b> | 14.0     |                |      |
| <b>RC (IN)</b>  | 93.3     |                |      |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI      | 125  |
|----------------|------|
| 62 LOAD SINGLE | 4805 |
| 62 LOAD DUAL   | 4540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.