

# TR 315

<b>TIRE SIZE</b>	<b>23X10.50 - 12</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / МАШИНА ДЛЯ СБОРА ФРУКТОВ / ТРАНШЕЙНЫЙ ЭКСКАВАТОР / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94070381	<b>RC (IN)</b>	72.4
<b>SW (IN)</b>	10.0	<b>RIM REC</b>	8½ JA
<b>OD (IN)</b>	23.6	<b>RIM ALT</b>	7 JA
<b>SLR (IN)</b>	10.7	<b>ECE</b>	E11-106R-007639

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>66</b>
10	2680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.