

# AT 621

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 17.5/65 - 20   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | ❖ BIAS   |
| <b>MACHINERY</b>    | CARREGADORA COMPACTA /<br>RETROESCAVADORA /<br>RETROESCAVADORA / CARREGADORA |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSÕES IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 450  | <b>RIM REC</b>  | W 14 L          |
| <b>OD (MM)</b>  | 1090 | <b>ECE</b>      | E11-106R-005262 |
| <b>SLR (MM)</b> | 490  | <b>PR</b>       | 10              |
| <b>RC (MM)</b>  | 3294 | <b>TRA CODE</b> | R4              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.40</b> |
| 10                | 3150        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.