

# FLOTATION 648

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>400/60 - 22.5</b>  |
| <b>UM</b>                 | IS STANDARD   |
| <b>CONSTRUCTION</b>       | BIAS  |
| <b>MACHINERY</b>          | ENFARDADEIRA DE FENO / CEIFEIRA /<br>ESPALHADOR / CEIFEIRA /<br>IMPLEMENTOS AGRÍCOLAS |
| <b>VERSÃO</b>             | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 148 A8/144 B  |
| <b>LI/SS FREE ROLLING</b> | 160 A8/ 156 B   |



## DIMENSÕES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 400  | <b>RIM REC</b> | AG 11.75       |
| <b>OD (MM)</b>  | 1070 | <b>ECE</b>     | E4-106R-002264 |
| <b>SLR (MM)</b> | 475  | <b>PR</b>      | 18             |
| <b>RC (MM)</b>  | 3233 |                |                |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.80 | 4.00 | 4.30 |
|------------|------|------|------|
| 10 FR      | 5860 | 6040 | 6300 |
| 20 FR      | 5275 | 5435 | 5670 |
| 30 FR      | 4685 | 4835 | 5040 |
| 40 FR      | 4185 | 4315 | 4500 |
| 50 FR      | 3765 | 3885 | 4000 |
| 10 DW      | 4100 | 4230 | 4410 |
| 20 DW      | 3690 | 3805 | 3970 |
| 30 DW      | 3280 | 3380 | 3530 |
| 40 DW      | 2930 | 3020 | 3150 |
| 50 DW      | 2635 | 2720 | 2800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.