

# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>420/70 R 30</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | BESPRUTNINGSBIL / TRAKTOR /<br>SKÖRDEMASKIN FÖR VINGÅRD /<br>SKÖRDEMASKIN / ARBETSFORDON |
| <b>VERSION</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 134 D  |



## DIMENSIONER IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 418  | <b>RIM REC</b> | W 13            |
| <b>OD (MM)</b>  | 1398 | <b>RIM ALT</b> | W 12; W 14 L    |
| <b>SLR (MM)</b> | 631  | <b>ECE</b>     | E11-106R-005830 |
| <b>RC (MM)</b>  | 4172 | <b>SRI</b>     | 675             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 65         | 1170 | 1360 | 1550 | 1740 | 1930 | 2120 |
| 50         | 1230 | 1430 | 1630 | 1830 | 2030 | 2230 |
| 40         | 1280 | 1490 | 1700 | 1910 | 2120 | 2325 |
| 30         | 1345 | 1565 | 1785 | 2005 | 2225 | 2440 |
| 10 LT      | 1565 | 1825 | 2080 | 2335 | 2590 | 2845 |
| 10 HT      | 1345 | 1565 | 1785 | 2005 | 2225 | 2440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.