

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 32</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	126 A8/B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	329	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	1357	<b>RIM ALT</b>	W 9 ; W 10
<b>SLR (MM)</b>	621	<b>ECE</b>	E4-106R-000758
<b>RC (MM)</b>	4081	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	935	1090	1245	1395	1550	1700
40	935	1090	1245	1395	1550	1700
30	1005	1165	1330	1495	1660	1820
10 LT	1255	1460	1665	1870	2075	2280
10 HT	1005	1165	1330	1495	1660	1820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.