

WASTEMAX



WASTEMAX

WASTEMAX is a solid tyre developed by BKT for wheel loaders operating at scrap yards, waste handling facilities, and demolition sites.

The tyre's solid construction significantly reduces the risk of tyre failure from cuts, punctures, and chunks caused by sharp debris, making WASTEMAX a highly cost-effective solution. Moreover, the particularly cut-and-chip-resistant compound offers exceptional protection against abrasive materials, while the deep tread design maximizes tyre life and reduces machine downtime.

WASTEMAX features a reinforced bead structure that prevents rim slippage in challenging waste-handling operations. In addition, sidewall apertures provide an excellent cushioning effect, ensuring a smoother ride and improved operator comfort during long service hours.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø25"	23.5 - 25 (605/80-25)	-	-	-		19.50/2.5	-	0	600	1630			216	CIR
NEW	23.5 - 25 (605/80-25)	-	-	-		19.50/2.5	-	0	600	1630			216	ELP
NEW	26.5 - 25 (685/80-25)	-	-	-		22.00/3.0	-	0	690	1715			236	CIR

CIR: CIRCULAR, ELP: ELLIPTICAL

TECHNOLOGIES		PERFORMANCES	
			
			


Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 01/10/2026



TECHNOLOGIES



PERFORMANCES



Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 01/10/2026