


# FL 630 SUPER

<b>TIRE SIZE</b>	<b>600/55 R 26.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRIDARE / TANKBIL / SLÄPVAGN / ARBETSFORDON
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	165 D



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94040476	<b>RC (IN)</b>	160.6
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	52.5	<b>ECE</b>	E4-106R-001414
<b>SLR (IN)</b>	23.9		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	3320	3840	4340	5280	6110	7030	7970	8590	9510	10340
40	3640	4210	4770	5800	6700	7730	8750	9420	10450	11350
30	4410	5090	5780	7010	8110	9350	10590	11420	12650	13750
25	4950	5720	6490	7880	9120	10500	11890	12820	14210	15440
15	5740	6650	7540	9160	10590	12210	13820	14900	16510	17940
5	6550	7570	8590	10430	12060	13900	15740	16960	18800	20440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.