


# AGRIMAX FORCE

**IF 900/60 R 38**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BIÇERDÖVER / YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	184 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94038749	<b>RC (IN)</b>	240.4
<b>SW (IN)</b>	36.1	<b>RIM REC</b>	DW 30 A; DW 30 B
<b>OD (IN)</b>	80.5	<b>RIM ALT</b>	TW 31 B
<b>SLR (IN)</b>	35.6	<b>ECE</b>	E11-106R-006493

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	8300	9570	11010	12270	13710	14980	16790	18050
<b>FROM 40 TO 25</b>	9130	10520	12100	13490	15080	16470	18450	19800
20	9490	10930	12580	14020	15670	17120	19180	20630
12	9850	11350	13060	14560	16280	17780	19920	21430
5	11580	13350	15370	17130	19150	20910	23420	25200
<b>UPTO 20 CYC</b>	11860	13670	15730	17540	19600	21410	23980	25790
<b>UPTO 10 CYC</b>	14140	16290	18750	20910	23370	25520	28590	30750
<b>UPTO 5 CYC</b>	15510	17870	20570	22930	25630	27990	31360	33730
5 HT	9490	10930	12580	14020	15670	17120	19180	20630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.